

PA - FOC

QUERY CONTROL FORM			RTIS USE ONLY	
Application No. <u>09519599</u>	Prepared by <u>TW</u>	Tracking Number <u>2868397</u>		
Examiner-GAU <u>Quach - 2014</u>	Date <u>3-24-04</u>	Week Date <u>12-1-03</u>		
	No. of queries <u>1</u>			

IFW

JACKET			
a. Serial No.	f. Foreign Priority	k. Print Claim(s)	p. PTO-1449
b. Applicant(s)	g. Disclaimer	l. Print Fig.	q. PTOL-85b
c. Continuing Data	h. Microfiche Appendix	m. Searched Column	r. Abstract
d. PCT	i. Title	n. PTO-270/328	s. Sheets/Figs
e. Domestic Priority	j. Claims Allowed	o. PTO-892	t. Other

SPECIFICATION	MESSAGE
a. Page Missing	
b. Text Continuity	On Page 4, Line 12 makes a reference to a
c. Holes through Data	Figure 10 but there is no Figure 10 in the drawing
d. Other Missing Text	sheet of this file.
e. Illegible Text	
f. Duplicate Text	
g. Brief Description	
h. Sequence Listing	
i. Appendix	
j. Amendments	
<input checked="" type="radio"/> Other	
CLAIMS	
a. Claim(s) Missing	
b. Improper Dependency	Please verify
c. Duplicate Numbers	
d. Incorrect Numbering	
e. Index Disagrees	
f. Punctuation	
g. Amendments	
h. Bracketing	
i. Missing Text	
j. Duplicate Text	
k. Other	
	RESPONSE
	Corrected.
	initials JBH

barrier metal layer are adversely affected.

Peeling-off of the organic insulating film of a low dielectric constant easily occurs, because of poor adhesion to a silicon wafer or SiO_2 film. Furthermore, the organic insulating film has the disadvantage that its heat resistivity is low. Its thermal decomposition temperature is around 400°C . The disadvantage of low heat resistivity poses a problem for annealing a wafer at a high temperature.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a method for forming an interlayer insulating film having good moisture absorption resistance, good heat resistivity and a low dielectric constant, a semiconductor device using the interlayer insulating film, and a semiconductor manufacturing apparatus for forming the interlayer insulating film.

JBH
3-24-04
According to the method for forming the interlayer insulating film according to the present invention, as illustrated in FIG. ^{1C}~~10~~, the film is formed on a substrate by plasma enhanced chemical vapor deposition using a source gas (or a reaction gas) containing a Si-C-O-H compound, O_2 and B_2H_6 . B (boron), C (carbon) and H_2O are contained in the film thus formed. The inventor found that when this film is annealed using an O (oxygen) plasma, C (carbon) and H_2O in the film are released from the film and thus many voids are created in the film, as illustrated in FIG. 1D. Thus, a porous SiO_2 film containing B (boron) can be formed on the